



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

## Protect It! 6-Outlet Surge Protector, 6-ft Cord, 790 Joules, Diagnostic LED

MODEL NUMBER: **TLP606**



### Highlights

- 6 outlet / 6-ft. cord
- 790 joule rating
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- TLP606 surge suppressor
- Instruction manual with warranty information

### Description

Tripp Lite's TLP606 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP606 offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 790 joules shields equipment from surges and line noise. Attractive light grey suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 6 NEMA5-15R/6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/790 joules/400V UL1449 3rd Edition

### Features

- 6 outlets
- 6-ft. cord
- Surge suppression rating: 790 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| OUTPUT                             |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Frequency Compatibility            | 50 / 60 Hz                                                                                                         |
| Output Receptacles                 | (6) 5-15R                                                                                                          |
| Output (Watts)                     | 1800                                                                                                               |
| Circuit Breaker (amps)             | 15                                                                                                                 |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                                                          |
| Transformer Accommodation          | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 3 transformers total |
| Outlet Orientation                 | Single row of 6 outlets                                                                                            |
| Right-Angle Outlets                | No                                                                                                                 |
| INPUT                              |                                                                                                                    |
| Nominal Input Voltage(s) Supported | 120V AC                                                                                                            |
| Recommended Electrical Service     | 120V (110-125V)                                                                                                    |
| Input Connection Type              | NEMA 5-15P                                                                                                         |
| Input Cord Length (ft.)            | 6                                                                                                                  |
| Input Cord Length (m)              | 1.83                                                                                                               |
| Input Cord Gauge Type              | 14 gauge, SJT                                                                                                      |
| Voltage Compatibility (VAC)        | 120                                                                                                                |
| Maximum Surge Amps                 | 35500                                                                                                              |
| Right-Angle Plug                   | No                                                                                                                 |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                                                    |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch                                  |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status                                               |
| SURGE / NOISE SUPPRESSION          |                                                                                                                    |
| AC Suppression Joule Rating        | 790                                                                                                                |
| AC Suppression Response Time       | < 1 ns                                                                                                             |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                 |
| Clamping Voltage (RMS)             | 150                                                                                                                |
| UL1449 Let Through Rating          | 500V                                                                                                               |
| DATALINE SURGE SUPPRESSION         |                                                                                                                    |
| Telephone/DSL Protection           | No                                                                                                                 |
| Cable (Coax) Protection            | No                                                                                                                 |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                            |                                                                     |
|------------------------------------------------------------|---------------------------------------------------------------------|
| Network (Ethernet) Protection                              | No                                                                  |
| <b>PHYSICAL</b>                                            |                                                                     |
| Shipping Dimensions (hwd / in.)                            | 13.2 x 5 x 1.80                                                     |
| Shipping Dimensions (hwd / cm)                             | 30.99 x 11.99 x 3.78                                                |
| Shipping Weight (lbs.)                                     | 1.20                                                                |
| Shipping Weight (kg)                                       | 0.53                                                                |
| Unit Dimensions (hwd / in.)                                | 10.8 x 1.85 x 1.23                                                  |
| Unit Dimensions (hwd / cm)                                 | 3.20 x 4.19 x 26.29                                                 |
| Unit Weight (lbs.)                                         | 1.01                                                                |
| Unit Weight (kg)                                           | 0.48                                                                |
| Material of Construction                                   | Plastic                                                             |
| Integrated Keyhole Mounting Tabs                           | Keyhole mounting tabs enable wall mounting                          |
| Housing Color                                              | Light Gray                                                          |
| Receptacle Color                                           | Light Gray                                                          |
| Color (AC Line Cord)                                       | Light Gray                                                          |
| Outlets Measurement (Center to Center)                     | 28.5mm                                                              |
| Keyhole Slot Mounting Measurement (Center to Center)       | Distance between slots = 101mm; Distance between slot height = 28mm |
| <b>CERTIFICATIONS</b>                                      |                                                                     |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd EDITION                                                  |
| UL1363 (Power Tap)                                         | UL1363                                                              |
| cUL / CSA (Canada)                                         | cUL                                                                 |
| Approvals                                                  | Exceeds IEEE 587 category A&B specifications                        |
| <b>WARRANTY</b>                                            |                                                                     |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                           |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 <a href="#">Ultimate Lifetime Insurance</a>                |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>