



Overview

| | |
|----------------------|---|
| Model Name | APC Power Saving Back-UPS Pro 1500 |
| Includes | CD with software , USB cable , User Manual |
| Standard Lead Time | Usually in Stock |
| Product Distribution | Anguilla , Aruba , Bahamas , Barbados , Belize , Bermuda , Canada , Colombia , Costa Rica , Cuba , Dominican Republic , Ecuador , El Salvador , Grenada , Guatemala , Guyana , Haiti , Honduras , Jamaica , Madagascar , Mauritius , Mayotte , Mexico , Netherlands Antilles , Nicaragua , Panama , Puerto Rico , Reunion , Trinidad And Tobago , Turks And Caicos Islands , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES) |

Output

| | |
|----------------------------------|---|
| Output Power Capacity | 865 Watts / 1500 VA |
| Max Configurable Power (Watts) | 865 Watts / 1500 VA |
| Nominal Output Voltage | 120V |
| Output Frequency (sync to mains) | 50/60Hz +/- 3 Hz |
| Output Frequency (sync to mains) | Line Interactive |
| Waveform Type | Stepped approximation to a sinewave |
| Output Connections | (5) NEMA 5-15R (Battery Backup) , (5) NEMA 5-15R (Surge Protection) |

Input

| | |
|------------------------|------------------------------------|
| Nominal Input Voltage | 120V |
| Input Frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | NEMA 5-15P |
| Cord Length | 6 feet (1.83 meters) (1.83 meters) |
| Maximum Input Current | 0 A |
| Input Breaker Capacity | 0 A |

Batteries & Runtime

| | |
|--------------------------|--|
| Battery Type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Included Battery Modules | 1 |
| Battery Slots Empty | 0 |
| Typical recharge time | 8 hour(s) |
| Replacement Battery | APCRBC124 |

| | |
|--------------|---|
| RBC Quantity | 1 |
|--------------|---|

Communications & Management

| | |
|---|--|
| Interface Port(s) | USB |
| Available SmartSlot™ Interface Quantity | 0 |
| Control panel | Multi-function LCD status and control console |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|----------------------|---|
| Surge energy rating | 354 joules |
| Filtering | Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: instantaneous |
| Data Line Protection | Cable modem / Video protection , Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector) |

Physical

| | |
|----------------------|------------------------------------|
| Maximum Height | 11.85 inches (301.0 mm) (301.0 mm) |
| Maximum Width | 4.41 inches (112.0 mm) |
| Maximum Depth | 15.04 inches (382.0 mm) (382.0 mm) |
| Rack Height | 0 U |
| Net Weight | 26.62 lbs (12.1 kg) (12.1 kg) |
| Shipping Weight | 29.37 lbs (13.35 kg) (13.35 kg) |
| Shipping Height | 15.24 inches (387.0 mm) (387.0 mm) |
| Shipping Width | 9.37 inches (238.0 mm) (238.0 mm) |
| Shipping Depth | 19.21 inches (488.0 mm) (488.0 mm) |
| Master Carton Units | 1.0 |
| Master Carton Weight | 0.0 lbs |
| SCC Codes | 1073130426877 9 |
| Units per Pallet | 20.0 |

Environmental

| | |
|---|--|
| Operating Environment | 32 - 104 °F (0 - 40 °C) (0 - 40 °C) |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-30000 feet (0-9000 meters) (0-9000 meters) |
| Storage Temperature | 5 - 113 °F (-15 - 45 °C) (-15 - 45 °C) |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-50000 feet (0-15000 meters) (0-15000 meters) |
| Audible noise at 1 meter from surface of unit | 45.000 dB |

Conformance

| | |
|-----------------------------|---|
| Approvals | ENERGY STAR (USA) , FCC Part 15 Class B , NOM , TUV , UL 1778 |
| Standard warranty | 3 years repair or replace |
| Equipment protection policy | Lifetime : \$150000 |

Sustainable Offer Status

| | |
|-------|--------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |