

# Product data sheet

## Characteristics

# AP8702S-NA

Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.



## Purchase

APC  
 [AP8702S-NA](#)

## Overview

Description	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Model Name	Power Cord Kit (6 ea), Locking, C13 to C14, 0.6m, North America
Standard Lead Time	Usually in Stock
Product Distribution	Antigua And Barbuda , Anguilla , Netherlands Antilles , Argentina , Aruba , Barbados , Bermuda , Bolivia , Brazil , Bahamas , Belize , Canada , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , Falkland Islands (Malvinas) , Grenada , Guatemala , Guyana , Honduras , Haiti , Jamaica , SAINT KITTS AND NEVIS , Cayman Islands , SAINT LUCIA , Mexico , Nicaragua , Panama , Peru , Puerto Rico , Paraguay , El Salvador , Trinidad And Tobago , United States , Uruguay , SAINT VINCENT AND THE GRENADINES , Venezuela , VIRGIN ISLANDS (UNITED STATES)

## Output

Maximum Total Current Draw per Phase	10 A
Output Connections	(1) IEC 320 C13 (Battery Backup)
Cord Length	0.61 meters

## Input

Input Connections	IEC-320 C14
Cord Length	0.61 meters
Number of Power Cords	6
Maximum Line Current per phase	10 A
Maximum Input Current per phase	10 A

## Physical

Net Weight	0.7 kg
Maximum Height	240 mm
Maximum Width	70 mm
Maximum Depth	40 mm
Shipping Weight	0.7 kg
Shipping Height	240 mm
Shipping Width	70 mm
Shipping Depth	40 mm
Color	Black

## Environmental

Operating Environment	0 - 105 °C
Operating Relative Humidity	20 - 80 %
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 105 °C
Storage Relative Humidity	20 - 80 %
Storage Elevation	0-15000 meters

## Conformance

Approvals	CSA , UL Listed
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs